





Personal Tracker	Network	Messaging options	Waterproof / shock tolerance	Operating Temperature and Altitude	Power supply	Additional power supply options	Dimensions
SPOT2 	Globalstar satellite	Ok, Help, SOS, preconfigurable additional message	Waterproof, submersible up to 5m for 1 hour	-30°C to 60°C -100m to 6500m	Lithium batteries	---	9.4 x 6.6 x 2.5 cm 147.4 g
GoSafe 	Mobile phone network	HELP, mobile phone function to three preconfigurable telephone numbers	No	-20° C to 55°C	Lithium battery	AC adapter	1.2 x 2 x 4.9 cm 98 g
Solaradata 2000 	Iridium satellite	SMS texting, SOS	Waterproof, survives 2 m drop	-40° C to 50°C	NiMH batteries, Lithium batteries on request	Solar Panel, AC adapter, car charger	15 x 8 x 5 cm 650 g
Solardata 2100 	Iridium satellite	SMS texting, SOS	Waterproof, submersible up to 1m for 1 hour, survives 1 m drop, floats in water	-40° C to 60°C up to 13,000 m	NiMH batteries, Lithium batteries on request	Solar Panel, AC adapter, car charger	18 x 7.5 x 4.5 cm Approx. 500 g